

# E-SCREEN with KOOLBLACK™ Technology

**MERMET** MERMET is a registered trade mark of Mermet S.A.

- Composition: 36% Fibreglass | 64% PVC
- Fire Classification: NFPA 701-10 TM#1, California U.S. Title 19, CAN/ULC-S109-03 Small Flame Test  
AWTA tested AS/NZ 1530.2 & 1530.3
- Width: 3100mm (All Colours) | 2500mm (Available on Indent)
- Openness Factor: 5% average
- Weight: 358gsm +/- 5%
- Thickness: 0.47mm +/- 5%
- Pattern: Basketweave 2 x 2
- Stiffness: 62mm +/- 5mm
- Breaking: Warp >1900N | Weft >1200N (AS 2001.2.3) (Strength)
- Tear Resistance: AS 2001.2.10 Warp 25N | Weft 29N
- Colour Fastness: 6-7 Blue Scale (AS2001.4.21)
- Health/Safety: Fabric has been tested and does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Building Council of Australia (IEQ-11)
- Cutting Method: Ultrasonic | Knife | Crush | Pressure Cut





  
[www.norfolkblinds.com.au](http://www.norfolkblinds.com.au)  
[info@norfolkblinds.com.au](mailto:info@norfolkblinds.com.au)  
 1300 557 544

E-SCREEN with KOOLBLACK™ Technology



E-SCREEN with  
KOOLBLACK™ Technology

Suitable for **GREEN** Buildings



COMMERCIAL  
EDUCATION  
HEALTH CARE



Used in  axis signature |  axis hercules |  axis box Systems