

# GREENSCREEN® NRG

© Registered Trade Marks of Hunter Douglas Limited.

Composition: 100% Polyester Trevira CS  
Width: 2900mm Greenscreen® NRG Plain Weave  
2400mm Greenscreen® NRG Metallised  
Openness Factor: 3% average  
Weight: 216gsm +/- 10  
Thickness: 0.49mm +/- 5mm Plain Weave  
0.40mm +/- 5mm Metallised  
Stiffness: 55mm +/- 5  
Colour Fastness: 6-7 AS 2001.4.21  
Breaking Strength: Warp > 1000N | Weft 800N AA 2001.2.3.1988  
Tear Resistance: Warp > 60N | Weft 50N AS 2001.2.10  
Fire Retardant: Independently tested to AS 1530.2 & 1530.3  
Suitable for Class 2 -9 (a) & (c) buildings as per BCA

**5 YEAR WARRANTY**

Suitable for **GREEN Buildings\*** - Greenscreen NRG Metallised


   
www.norfolkblinds.com.au  
info@norfolkblinds.com.au  
1300 557 544

GREENSCREEN® NRG

  
norfolkblinds 

GREENSCREEN® NRG

Suitable for **GREEN Buildings\***



ROLLER  
BLINDS



PANEL GLIDE  
BLINDS

COMMERCIAL  
EDUCATION  
HEALTH CARE

 green building council australia  
MEMBER 2016-2017  
norfolkblinds

Used in  axis signature |  axis hercules |  axis box Systems